



**North American**  
**ADHESIVES®**

**NA 5200**

# Color Fill™ Caulk S

**Sanded Siliconized Acrylic Caulk**



## PRODUCT DESCRIPTION

*NA 5200 Color Fill Caulk S* is a premium-grade, easy-to-use, easy-to-clean siliconized acrylic caulk formulated to match the most popular North American Adhesive (NAA) grout colors.

## FEATURES AND BENEFITS

- Water cleanup while fresh
- Paintable
- Packaged in gun-grade tubes for easy application
- Mildew-resistant
- VOC-compliant

## USES

- For gaps up to 1/4" (6 mm)
- As a flexible barrier/filler between horizontal and vertical surfaces to prevent cracked tile due to expansion
- For filling joints where tile abuts dissimilar surfaces
- For caulking around sinks, tubs, showers, countertops and ceramic tile floors
- For interior use only
- For restoring cracked or worn grout joints

## SUBSTRATE REQUIREMENTS

- Substrates must be structurally sound, stable, clean and free from dust, oil, grease, paint, gypsum patch, flooring adhesive, tar, wax, sealers, curing compounds, form-release agents, laitance, loose particles and foreign substances that could reduce or impair adhesion.
- Remove all traces of paint, loose particles, residue and cement particles by mechanical means.
- Remove mildew by scrubbing with a mixture of 4 U.S. oz. (118 mL) of trisodium phosphate (TSP), 1 U.S. qt. (946 mL) of liquid bleach and 3 U.S. qts. (2.84 L) of warm water. Protect eyes and hands by wearing goggles

and water/chemical-resistant gloves. Thoroughly rinse and allow surface to dry completely before caulking and painting.

- Vacuum out joints and wipe them clean with a damp rag.

Consult Technical Services for installation recommendations regarding substrates and conditions not listed.

## LIMITATIONS

- Do not install over substrates containing asbestos.
- The application temperature range is 50°F to 90°F (10°C to 32°C).
- Apply only to clean, dry surfaces.
- Joints should not exceed 1/4" (6 mm) in width.
- Do not use for exterior projects or applications subject to constant water immersion.
- Do not use in areas where joints will be subject to heavy abrasion or wear.
- Allow new concrete to cure for 30 days before caulking.
- Although *NA 5200 Color Fill Caulk S* is color-matched to NAA's grout-color system, expect a slight variation in color due to the difference in composition between materials.
- For applications beyond 1/4" (6 mm) in depth, the caulking depth must be controlled by a closed-cell backer rod.
- To ensure product effectiveness, do not apply *NA 5200 Color Fill Caulk S* thinly, as with a paint.
- *NA 5200 Color Fill Caulk S* may stain porous materials. Test on a separate area before final application.
- Refer to the project's ASTM requirements before commercial use of *NA 5200 Color Fill Caulk S*.

## APPLICATION

- Tile should be firmly set before caulking. Typically, this is 24 to 48 hours after tile installation.
- Caulking may be done either before or after grouting.

**NA 5200**

# Color Fill™ Caulk S

- For a clean, straight and neat caulk joint, mask both sides of the joint with masking tape.
- NA 5200 Color Fill Caulk S is ready to use. Apply with a caulking gun. Do not open cartridges until preparatory work has been completed.
- Cut the nozzle tip to the desired bead size at a 45-degree angle.
- Completely fill joints with sealant and smooth over with a wet finger.
- Excess caulk should be removed with a damp cloth before the caulk skins over.
- Immediately wash hands and tools with warm water and soap.

**PROTECTION**

- Allow 24 hours of drying time before painting.
- Protect from water exposure until fully cured at least 72 hours.

Note: Larger beads of caulk and cool, humid conditions will require a longer drying time.

<b>Product Characteristics*</b>	
at 73°F (23°C) and 50% relative humidity	
Colors	Available in 16 colors
Packaging	Tube: 10.5 U.S. oz. (311 mL)
VOCs (Rule #1168 of California's SCAQMD)	< 25 g per L
Shelf life	1 year when stored in original, unopened packaging
Drying time	24 to 48 hours

\* Cold temperature or high humidity may alter these properties.

<b>Approximate Coverage**</b> per 10.5 US oz. (311 mL)	
Joint Size	Coverage
1/16" (1.5 mm)	48 to 50 lin. ft. (14.6 to 15.2 m)
1/8" (3 mm)	24 to 25 lin. ft. (7.32 to 7.62 m)
3/16" (4.5 mm)	15 to 17 lin. ft. (4.57 to 5.18 m)
1/4" (6 mm)	11 to 13 lin. ft. (3.35 to 3.96 m)

\*\* Coverage shown is for estimating purposes only. Actual jobsite coverage may vary depending on the joint size and application procedures.

**LEGAL NOTICE**

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in effect at the time of the NAA product installation. For the most up-to-date TDS and warranty information, visit our Website at [www.na-adhesives.com](http://www.na-adhesives.com). **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED NAA WARRANTIES.**

Before using, the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**